Developing Long-Term, Daily Datasets of Evaporative Demand for the Conterminous US

Michael Hobbins[1], David Streubel[2], Kevin Werner[1], David Brandon[2]

[1] Colorado Basin River Forecast Center/NWS/NOAA, Salt Lake City, UT 84116

[2] Hydrology and Climate Services Division, Western Region Headquarters/NWS/NOAA, Salt Lake City, UT 84103

Abstract:

Operational hydrologists and agriculturalists often seek to predict actual evapotranspiration (*ET*) fluxes. However, as they can seldom characterize actual moisture conditions in the soil and vegetation regimes, they are unable to estimate or forecast *ET* directly. Instead, they first estimate evaporative demand (E_o) (sometimes known as "potential *ET*") as an upper limit to actual *ET* and then apply E_o to drive hydrologic models or empirical relations that account for soil moisture conditions and vegetative constraints on moisture transfer, and thereby derive *ET*.

There are various formulations of E_o, with a wide variety of data requirements and philosophies, and, consequently, of scientific and operational validity. Here we summarize the ongoing development and uses of two daily time-series of E_o that are scientifically defensible, long term (30+ years), and CONUS-wide. Ultimately, these time-series will be unbiased with respect to the observations they seek to model and at a fine spatial resolution. These datasets are currently under development with two goals in mind: (i) to improve streamflow forecasting in the NWS River Forecast System, which would be of use to operational hydrologists, and (ii) to provide reference crop *ET* forecasts to NWS end-users, primarily agriculturalists.

Two goals:

1. Improve streamflow forecast skill across the Colorado River Basin at daily and water-supply-season time-scales (April 1 to July 31) by improving the evaporation driver (E_o) in the NWS River Forecast System.

This will entail (i) replacing the current static E_o (Fig 5) in the Sacramento Soil Moisture Accounting (SAC-SMA) model [Ref 1] with a physically based, temporally dynamic E_o that reflects ongoing weather-scale variability; (ii) simulating streamflows from the SAC-SMA model across the period 1980 – 2009; (iii) and recalibrating the SAC-SMA model to adapt the evaporation-related parameters to the new data input; in order to (iv) maximize the streamflow forecast skill score.

2. Provide forecast end-users across the NWS Western Region with forecasts of reference crop *ET* (ET_{rc}) at daily to weekly time-scales. This is driven primarily by demand from end-users in agriculture who seek guidance in making decisions regarding near-term water demand.

Our goal here is two-fold: (i) to provide a new *ET*-related forecast system using only currently forecast weather variables; and (ii) to provide a climatological context for these forecasts, as most users would otherwise be unfamiliar with what it represents.

These will be the first large-scale operational ET_{rc} forecasts.

Model drivers:

We need two sets of drivers:

1. Reanalysis data drive the SAC-SMA simulations in Goal 1 and the ET_{rc} climatology in Goal 2.
2. Forecast data drive the short-term ET_{rc} forecasts in Goal 2.

1. Reanalysis: North American Land Data Assimilation System (NLDAS) [Refs 2, 3]
- Air temperature at 2-m elevation, *T* (K)
- Specific humidity at 2-m elevation, *q* (kg/kg)
- Down-welling short-wave radiation, SW_{dn} (W/m^2)
- Down-welling long-wave radiation, LW_{dn} (W/m^2)
- Station pressure, P_{atm} (Pa)
- Wind speed at 10-m elevation, U_{10} (m/sec)
- Hourly time-step
- 0.125-deg (~12 km) resolution

2. Forecast: National Digital Forecast Database (NDFD) [Ref 4]
- Air temperature at 2-m elevation, *T* (F)
- Dewpoint temperature at 2-m elevation, T_{dew} (F)
- Wind speed at 2-m elevation, U_2 (m/sec)
- Areal extent of cloud cover, *ECA* (%)
- Hourly, 3-hourly, or 6-hourly time-steps
- 2.5-km or 5-km resolution

Model variables:

Output variables:

E_{pan} = synthetic pan evaporation (in mm/day)
ET_{rc} = reference crop evapotranspiration (in mm/day)

Input variables:

λ = latent heat of vaporization (from NLDAS *T* or NDFD *T*)
Δ = saturated vapor pressure-temperature relation slope (from *T*)
a_p = ratio of the effective surface areas for heat and water-vapor transfer in a pan
γ = psychrometric constant (from *T*, P_{atm})
Q_n = net available energy for evaporation (from NLDAS: SW_{dn}, LW_{dn}; NDFD: *ECA*, *T*)
$f_2(U_2)$ = vapor transfer function (from NLDAS: U_{10}; NDFD: U_2)
e_{sat} = saturated vapor pressure (from *T*)
e_a = actual vapor pressure (from NLDAS: *T*, *q*, P_{atm}; NDFD: T_{dew})
U_2 = wind speed at 2 m (from NLDAS U_{10} NDFD: U_2)

All input variables (SW_{dn}, LW_{dn}, U_{10}, *T*, P_{atm}, and *q*) are available as reanalyses (NLDAS) or forecasts (NDFD).

Goal 1: Improving streamflow forecast skill across the CBRFC

E_{pan} from the PenPan model of Linacre [Ref 5] modifies the familiar Penman equation [Ref 6] to replicate the enhanced characterization of radiative and advective dynamics of evaporation pans, as follows:

$$\lambda E_{pan} = \frac{\Delta}{\Delta + a_p\gamma} Q_n + \frac{a_p\gamma}{\Delta + a_p\gamma} f_2(U_2)(e_{sat} - e_a)$$

The formulation consists of a weighted combination of an radiative driver and an advective driver. It has been shown to synthesize monthly E_{pan} observations well [Ref 7].

A US class-A evaporation pan.



Daily evaporation driver across DRGC2. The red stepped line shows the current E_o driver, with no inter-annual variability; black lines show the inter-annual range of the new dynamic driver (daily E_{pan}) across 1980—2009, as the mean (bold black), maximum (upper black) and minimum (lower black). Also shown in blue is daily E_{pan} for an example year (1983).



Mean annual E_{pan} from the PenPan model, 1980 – 2009, expressed as mm depth.



The concept of the Sacramento Soil Moisture Accounting (SAC-SMA) model that underpins the NWS River Forecast System.



Right: Location of test-basin DRGC2 (red) in the San Juan river basin (small black outline) in the Colorado Basin River Forecast Center forecast region (large blue outline).

Left: Map of the test-basin, DRGC2: the Animas River at Durango, CO, showing basin relief and rivers.



Three hydrographs at DRGC2 for 1983: (i) the observed streamflow (black); (ii) the current static E_o driver with current operational calibration (blue); and the new dynamic E_{pan} driver with the evaporation-relevant parameters optimized (red).

The Root Mean Square Error Skill Score (RMSE-SS) can be used to assess the performance, or skill, of the SAC-SMA model in simulating (Q_{sim}) the observed daily streamflow (Q_{obs}). Here we compare the RMSE-SS for the current static E_o driver (shown in red in Fig 5) and the new dynamic E_o driver (shown in black in Figure 5), both with and without recalibration of the SAC-SMA model. The RMSE-SS derives as follows:

$$RMSE_{sim} = \sqrt{\frac{1}{N}\sum_{i=1}^{N}(Q_{sim_i} - Q_{obs_i})^2} \qquad RMSE\text{-}SS = 1 - \frac{RMSE_{sim}}{RMSE_{ref}}$$

A perfect simulation (Q_{sim} = Q_{obs}) yields an RMSE-SS of 1. A zero RMSE-SS indicates no change in skill as compared to the existing, or reference, simulation. A more skillful simulation yields a positive RMSE-SS, a less skillful simulation yields a negative RMSE-SS. The table below indicates the skill of each run, using the current RMSE from the static E_o driver run (the top-left entry in the table) as a reference ($RMSE_{ref}$). The most cogent comparison in this framework is that indicated in bold in the bottom-right entry.

RSME-SS compared		E_o type	
		current (static)	dynamic
SAC-SMA recalibration	none	(0.000)	-0.109
	SCE-UA optimization	-0.102	**-0.079**

- For the current static E_o driver, recalibrating the SAC-SMA model with the objective Shuffled Complex Evolution (SCE-UA) optimization method [Ref 10] reduces the skill when compared to the manual calibration used in current operations.
- For the new dynamic E_o driver, the objective SCE-UA method increases the skill.
- The system works. No operational or calibration issues were raised.
- These preliminary results suggest a way forward to improve the daily and seasonal streamflow forecast skills of the dynamic E_{pan} driver: an objective recalibration (e.g., the SCE-UA method) followed by subjective refinements by experienced CBRFC forecasters.

Goal 2: Forecasting ET_{rc} across the West

The reference crop *ET* (ET_o) formulation from the FAO-56 [Ref 8] international standard, the Penman-Monteith [Ref 9] equation is:

$$\lambda ET_{rc} = \frac{\Delta}{\Delta + \gamma(1 + 0.34U_2)} Q_n + \frac{\gamma}{\Delta + \gamma(1 + 0.34U_2)} \frac{0.9}{T} \frac{\lambda}{86400} U_2 (e_{sat} - e_a)$$

It consists of a weighted combination of a radiative driver and an advective driver.

The reference crop is specified:
- well-watered grass,
- actively growing,
- 0.12 m in height,
- completely shading the ground,
- albedo of 0.23.

ET_{rc} is then multiplied by various soil moisture, stress, and phenology factors known to the end-user, to yield an actual *ET* estimate, e.g.:

$$ET = k_s k_c(t) ET_{rc} \text{ or } (k_s k_{cb} + k_e)(t) ET_{rc}$$



Mean annual ET_{rc} from the Penman-Monteith model, 1980—2009, expressed as mm depth.



ET_{rc} concept: a standard crop under standard conditions is specified.

ET_{rc} concept: ET_{rc} is multplied by a series of factors that reflect (in this example) different crops, phenology, soil stress, etc.

Crop	$K_{c\,max}$	$K_{c\,mid\text{-}season}$	$K_{c\,end\text{-}of\text{-}season}$
Barley	0.30	1.15	0.25
Chickpea	0.40	1.00	0.35
Cotton	0.35	1.15-1.20	0.70-0.50
Maize	0.30	1.20	0.35
Navy bean	0.40	1.15	0.35
Peanut	0.40	1.15	0.60
Sorghum	0.30	1.00-1.10	0.55
Soybeans	0.40	1.15	0.50
Sunflower	0.35	1.15	0.35
Wheat	0.30	1.15	0.25

ET_{rc} concept: examples of crop coefficients K_c for various crops at various stages of growth.



Climatological ET_{rc} for a day in mid-August. Climatologies are NLDAS-derived for 1980—2009.

Forecast ET_{rc} for a day in mid-August, 2010. Forecasts are NDFD-derived.



ET_{rc} forecast delivery on the web. Available are maps of the NDFD-derived forecast, the NLDAS-climatology, and the forecast departure from normal (shown above), and a brief explanation of the ET_{rc} concept.



Current operational status of the ET_{rc} forecast system in the NWS Western Region. Roll-out across the region continues.

Conclusions & Current Accomplishments

We have created the first E_o reanalysis at an RFC-operational scale and resolution. A new forecast system for ET_{rc} is now operational and rolling out across the NWS Western Region. The ongoing reanalysis effort is yielding ET_{rc} estimates with a five-day latency, a short time-lag that renders it a potentially powerful new tool for real-time drought monitoring.

Goal 1: Improving streamflow forecast skill across the CBRFC: Thus far, we have proved the concept: the new dynamic E_{pan} driver of the SAC-SMA model can be seamlessly integrated into the NWS River Forecast System and there affects streamflow simulation skill. While first results over a single basin indicate a small decrease in simulation skill, a standard manual recalibration of the basin is most likely to result in significant skill improvement. Such a manual recalibration, while subjective, can balance various goals: forecasting on a daily basis (e.g., for low flows, peak-flow estimates and timings) versus water supply seasonal-volume forecasting.

Goal 2: Forecasting ET_{rc} across the western US: We have created a system to forecast daily-to-weekly ET_{rc}. While the project was initiated primarily with agricultural users in mind, it has generated significant interest from decision-makers at the state and regional levels. A verified, high-resolution, reanalyzed, and/or forecast ET_{rc} would be useful in short-term decision-making, drought analyses across time scales, and, in the longer term, demand-planning:

- The primary use of ET_{rc} is to assist farmers in making decisions regarding irrigation scheduling up to a week into the future.
- The US Drought Monitor currently has no physically based metric of evaporative demand. Instead, its PDSI input has a flawed *T*-based E_o driving its bucket model [Ref 11]. Incorporating near-real-time ET_{rc} reanalyses and forecast ET_{rc} directly into the Monitor would enhance its capabilities with respect to monitoring recent, ongoing, and future drought development. At longer time-scales, the analyses of long-term drought trends, such as using the popular Palmer Drought Severity Index (PDSI), have heretofore been stymied by the lack of long-term reanalyses of E_o.
- The increasingly uncertain hydrologic environment presents utility districts and operators of reservoirs and trans-mountain diversions with thorny strategic capital decisions. As a result, they are becoming increasingly interested in demand-planning and particularly in long-term forecasts of E_o.

Ongoing & Future work:

Operationally, the dynamic E_o-driven streamflow forecasting system (i.e., Goal 1) is still some time away from an active transition from research to operations at NWS River Forecast Centers. However, the ET_{rc} forecast system (i.e., Goal 2) is spreading across the NWS Western Region, with plans for CONUS-wide adoption.

We are expanding the dynamic E_o study to other models of evaporative demand, both physically based (e.g., the Penman, Penman-Monteith, and Kimberly Penman formulations) and temperature-based (e.g., the Hargreaves, Hamon, Thornthwaite, Blaney-Criddle formulations).

We are improving the reanalyses and forecasts by verifying both the drivers (particularly the derivation of SW_{dn} from *ECA*) and E_o (against observations of E_{pan} and ET_{rc} at CIMIS stations[3]), and generating finer-scale, longer-term reanalyses of evaporative demand that incorporate the 4-km spatial resolution of the Real-Time Mesoscale Analysis dataset and the over 30-year extent of the NLDAS dataset.

Future work on varied time-scales will include the incorporation of seasonal drivers (e.g., from the Climate Forecast System at NCEP) in order to provide better seasonal-scale water demand estimates, and on climate scales, incorporation of IPCC scenarios for climate-scale forecasts and strategic decision-making.

Scientific Contributions:

The new E_o datasets, when verified and at a finer resolution, suggest various scientific contributions. An ongoing study of the temporal and spatial variability of E_o should answer various questions: which drivers dominate the spatial and temporal variability of E_o? which E_o is best for hydrologic operations across CONUS? are temperature-based E_o-models ever preferred over physically based E_o models?

The rigorous, long-term reanalyses of streamflow and ET_{rc} should permit analyses of long-term trends in streamflow and drought across CONUS, identifying which physical driver dominates such trends, and make a significant contribution to the vexed issue of the effects of climate change and variability on hydrology across the Colorado Basin, thereby furthering the goals of the Colorado River Reconciliation project.

References:

1. Burnash, R.J., Ferral, R.L., McGuire, R.A., 1973, A generalized streamflow simulation system: Conceptual modeling for digital computers, U.S. Dept. of Commerce NWS and State of California Department of Water Resources.
2. Mitchell, K.E., D. Lohmann, P.R. Houser, E.F. Wood, J.C. Schaake, A. Robock, B.A. Cosgrove, J. Sheffield, Q. Duan, L. Luo, R.W. Higgins, R.T. Pinker, J.D. Tarpley, D.P. Lettenmaier, C.H. Marshall, J.K. Entin, M. Pan, W. Shi, V. Koren, J. Meng, B.H. Ramsay, and A.A. Bailey, 2004, The multi-institution North American Land Data Assimilation System (NLDAS): Utilizing multiple GCIP products and partners in a continental distributed hydrological modeling system, *J. Geo. Res.*, 109.
3. The NLDAS data used in this study were acquired as part of the mission of NASA's Earth Science Division and archived and distributed by the Goddard Earth Sciences (GES) Data and Information Services Center (DISC).
4. Glahn, H.R., and D.P. Ruth, 2003, The new digital forecast database of the National Weather Service, *Bull. Amer. Met. Soc.*
5. Linacre, E.T., 1994, Estimating U.S. class A pan evaporation from few climate data, *Water International*, 19: 5–14.
6. Penman, H.L., 1948, Natural evaporation from open water, bare soil and grass, *Proc. R. Soc.*, London, Ser. A, 120–146.
7. Rotstayn, L.D., M.L. Roderick, and G.D. Farquhar, 2006, A simple pan-evaporation model for analysis of climate simulations: Evaluation over Australia, *Geo. Res. Lett.*, 33, L17715.
8. Allen, R.G., L.S. Pereira, D. Raes, and M. Smith, 1998, Crop evapotranspiration: Guidelines for computing crop water requirements, *FAO Irrigation and Drainage Paper 56*, FAO, Rome.
9. Monteith, J.L., 1965, Evaporation and environment, in *The State and Movement of Water in Living Organisms*, Sympos. Soc. Exper. Biol., 19, edited by G. E. Fogg, pp. 205–234, Academic, San Diego, CA.
10. Duan, Q., V.K. Gupta, and S. Sorooshian, 1993, A shuffled complex evolution approach for effective and efficient global minimization, *J. Opt. Th. Appl.*, 61(3).